Benchmark Vortex Mixer | Conclusion | Conc



- Powerful Motor for INSTANT Vortexing
- 🕂 Q-Drive™Dynamic Balance System
- Touch or Continuous Operation
- Variable Speed Control from 200 to 3200rpm





Technical Data

 Speed Range:
 200 to 3200 rpm

 Operating Modes:
 Touch or continuous

 Operating Temp. Range:
 +4 C to +65 C

 Dimensions:
 13 x 16 x 17 cm

 5 x 6.3 x 6.7 in.
 5 x 6.3 x 6.7 in.

 Weight:
 3.8 kg / 8.4 lb

 Electrical:
 115V AC, 60 Hz, 1.5A

 230V AC, 50 Hz, 0.75A

2 years

The BenchMixer™ sets the new standard in vortex mixing. With advanced Q-Drive™ technology, the BenchMixer™ provides smooth instant vortexing of even the largest sample sizes, including full 50ml tubes. The unique counter balance system creates maximum

vortexing action, while minimizing noise and excessive vibration. This results in quieter, more efficient and longer lasting operation.

Other features include: "no-walk" suction feet, cold room/incubator compatibility and spill-proof electronic controls.

Ordering Information

Warranty:

BV1000*

BenchMixer Vortex Mixer

BV1000-FLAT BV1000-COMBO

Optional 3 inch flat head

Optional combination head for tubes and microplates. Holds 66 tubes (38 x 1.5ml and 28 x 0.5ml) or one microplate

* To order a product in 230V, please add -230 to item number.



Benchmark Scientific Inc. PO Box 709 Edison, NJ 08817 Phone: 908-769-5555 Fax: 908-222-1864

Web: www.BenchmarkScientific.com Email: Info@BenchmarkScientific.com